

# PEL-PLUG TR30/60

COATED BENTONITE PELLETS  
(U.S. Patent No. 5,476,543)



## DESCRIPTION

**Pel-Plug TR30/60** is a clean, virtually odorless and easy to handle bentonite pellet which combines the high quality yield of western bentonite with a biodegradable non-sticking coating. This coating, developed by PDSCo, allows the pellets to be poured through standing water without sticking together, eliminating voids and bridging. **Pel-Plug TR30/60** has the same ability to absorb water and maintain the 8-12 times expansion pattern that has been typical of our very successful regular Pel-Plug bentonite pellets. Pellets should be allowed to hydrate for at least 2 to 3 hours (depending on water quality).

## ADVANTAGES

1. Clean, dust-free, and easy to handle.
2. Non-toxic and non-polluting.
3. Can be poured directly into place for the highest density per cubic foot (accumulation) of any existing grouting method, dry or wet.
4. No mixing required; thus, eliminates the needs for large and expensive grouting units, problem of over mix, and reduces labor costs.
5. Do not disintegrate upon swelling; seals are tough but flexible, and do not crack when subjected to movement.

## RECOMMENDED USAGE

USAGE CHART	Hole Diameter	2"	3"	4"	5"	6"	7"	8"
	Lbs of pellets/ft of seal	1.75	4	7	11	16	22	28

**NOTE:** These are dry weights and volumes. In use, the swelling of the pellets will increase the length of the seal (depending on hole condition).

## PACKAGING

**Pel-Plug TR30/60** is packaged in 50 lb reusable, reseal able, and waterproof containers.

Pellets available in 1/4", 3/8", and 1/2" sizes.

Special order pellets are available to further retard pellet swell time during very deep water applications.

Please call for more details.

